

# HYDRAULIC TRAILERS



## SPECIFICATIONS

Model	3 Tonne	4 Tonne	5 Tonne	6 Tonne	8 Tonne	10 Tonne
Deck (L x W)	2.7m x 2.3m	3.3m x 2.3m	3.3m x 2.4m	3.6m x 2.4m	4.2m x 2.4m	4.6m x 2.4m
Sides	300mm Steel	300mm Steel	400mm Steel	400mm Steel	500mm Steel	600mm Steel
Floor	38mm Treated Pine	38mm Treated Pine	38mm Treated Pine	4mm Core-Ten Steel	4mm Core-Ten Steel	4mm Core-Ten Steel
Capacity	1.8m <sup>3</sup>	2.3m <sup>3</sup>	3.1m <sup>3</sup>	3.4m <sup>3</sup>	5.0m <sup>3</sup>	6.6m <sup>3</sup>
Axle Type	Single Axle 60mm	Single Axle 60mm	Single Axle 70mm	Tandem Axle 60mm	Tandem Axle 70mm	Tandem Axle 70mm
Axle Capacity	4,000kg	4,000kg	6,000kg	8,000kg	12,000kg	12,000kg
Wheels	11.5/80 x 15.3	11.5/80 x 15.3	11.5/80 x 15.3	11.5/80 x 15.3	400/60 x 15.5	400/60 x 15.5
Ram Type and Diameter	3" Single Stage	3.5" Single Stage	4" Single Stage	Four Stage	Five Stage	Five Stage
Jack Type	70mm screw jack	70mm screw jack	70mm screw jack	70mm screw jack	70mm screw jack	70mm screw jack
Tailboard	Standard	Standard	Standard	Standard	Standard	Standard
Hay Extension	Optional	Optional	Optional	Optional	Optional	Optional
Steel Deck	Optional	Optional	Standard	Standard	Standard	Standard

PROUDLY DESIGNED AND MANUFACTURED IN NEW ZEALAND BY

COOMBRIDGE & ALEXANDER LTD

visit [www.sammachinery.co.nz](http://www.sammachinery.co.nz)